

OUTRIGGER PADS



TEKNIK

LAVORAZIONE TECNOPOLIMERI

via Rossini 1, 20002

Asmonte di Ossona (MI), ITALY

T: 0039.02.90380361/561

E: info@technik.it

www.technik.it



HDPE high-density polyethylene

The HDPE Fine Black is a regenerated PE.

The percentage of recycled material is maximum 30%.

It guarantee the mechanical testing effort for the toughest lifting applications.

**HIGH
CAPACITY
LIFTING**



**CREATE
YOUR OWN
PAD**

Dimensions LxWxH (mm) SQUARE	Dimensions ROUND DIAM. (mm)	Load cap. (Kg)	Weight (Kg)
400 x 400 x 40		10000	6
400 x 400 x 60		12000	9
500 x 500 x 40		15000	10
500 x 500 x 50		15000	12
500 x 500 x 60		20000	14
600 x 600 x 40		20000	14
600 x 600 x 50		23000	18
600 x 600 x 60		25000	21
700 x 700 x 50		25000	24
800 x 800 x 40		25000	25
800 x 800 x 50		30000	31
1000 x 1000 x 40		30000	38
800 x 800 x 60		35000	38
1000 x 1000 x 50		40000	48
1000 x 1000 x 60		50000	58
1000 x 1000 x 70		65000	68
1000 x 1000 x 80		70000	74
1200 x 1200 x 80		90000	113
	DIA 800 x 60	30000	30
	DIA 1000 x 50	35000	38
	DIA 1000 x 60	40000	45
	DIA 1000 x 80	50000	61
	DIA 1200 x 80	70000	88

Tensile strength 27 MPa
Tensile modulus of elasticity 670 MPa
Elongation at break 200%
Shore Hardness D 67

Max service temperature 80 °C
Min service temperature -150 °C

**HIGH
STRENGTH**

